



## Collision Awareness LOOK OUT™



Each sensor has 11 electronic eyes that fan out beams to read an area of 32' by 42' wide.

### New State-of-the-Art Sensors

Our new infrared sensor debuted in 2011 allowing for 99.9% detection at 32', eliminating false alerts beyond that distance. The sensor sends out a "cone-shaped" beam that reads an area 32' out and 42' wide. The beam is supported by 11 electronic eyes that read this area simultaneously. Once two eyes have been violated, the warning devices will activate.



### Look Out 2, 3 & 4 (Hanging Mount)

- For 2, 3 or 4-way intersections to monitor and alert all directions
- Sensor range is 32' away and 42' wide, adequate distance to stop a fork truck traveling at OSHA recommended speeds
- 50' of standard cable
- Optional "Brilliant" light for mounts above 20'



### Save-Ty Product Features...

- Alerts pedestrians when forklifts are crossing
- Unit mounts up and out of the way
- No reflectors required
- No expensive microwave sensors
- Nothing attached to your forklifts
- Low voltage wiring eliminates the need for conduit. 24V transformer plugs into an overhead outlet power source
- Super bright LED lights with 100,000 hours life
- Sensors are factory pre-set to monitor from inches to 32' away. They may be adjusted in an up/down & side/side motion when installed for final detection area coverage
- Sound option for loud environments or outdoors
- Injuries & fatalities as a result of forklift collisions can be eliminated
- Universal transformer will handle incoming voltage from 277V to 24V as required
- Indoor, outdoor and cooler applications
- Significant loss prevention benefits
- Steel powder coated boxes for durability
- Available in Stainless Steel

**Industrial Safety Controls**

P.O. Box 126 • 4112 Sheridan Road, Kenosha, WI 53141

(262) 652-8660 • Fax: (262) 652-1388 • [www.safeworkplace.org](http://www.safeworkplace.org) • e-mail: [safetysensing@earthlink.net](mailto:safetysensing@earthlink.net)